ADII Ltd



10 second invisible ink

Page 1/7

Revision 2 Revision date 2016-07-14

SECTION 1: Identification of	of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	10 second invisible ink
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Description	Printing Ink.
1.3. Details of the supplier of the	ne safety data sheet
Company Address	ADII Limited Houldsworth Street Stockport Cheshire SK5 6DA
Telephone E-Mail	+44 (0) 7590 414092 john@acorndigital.co.uk
1.4. Emergency telephone num	
24 Hours	+44 (0) 7590 414092
SECTION 2: Hazards ident	ification
2.1. Classification of the substa	ance or mixture
2.1.1. Classification - 1999/45/EC Main hazards	Xi; R37-41 R10-52/53 Symbols: Xi: Irritant. Flammable. Irritating to respiratory system. Risk of serious damage to eyes. Harmful to aquatic
	organisms, may cause long-term adverse effects in the aquatic environment.
2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Eye Dam. 1: H318; STOT SE 3: H335; Aquatic Chronic 3: H412;
2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	 Flam. Liq. 3: H226 - Flammable liquid and vapour. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Copyright © 2016 ChemSoft Limited. All right	s reserved. Powered by Power



 Revision
 2

 Revision date
 2016-07-14

2.2. Label elements	
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse
Response	skin with water/shower.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
Precautionary Statement:	P403+P235 - Store in a well-ventilated place. Keep cool.
Storage	
2.3. Other hazards	

SECTION 3: Composition/information on ingredients

No data available.

3.2. Mixtures

Other hazards

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Cyclohexanone	606-000-007	108-94-1	203-631-1		70-80%	Flam. Liq. 3, H226: Tox 4: H333	
Trans Stilbene		103-30-0	203-098-5		3-4%	H315 cause	es skin irritation

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Cyclohexanone	606-000-007	108-94-1	203-631-1	7	′0-80%	Flam Liq 3. H226: Acute Tox 4: H332;)
Trans Stilbene		103-30-0	203-098-5	3-	-4%	H315 causes skin in	ritation

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Seek medical attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Treat as for inhalation if any signs of poisoning are present.
Ingestion	DO NOT INDUCE VOMITING. Seek medical attention.
4.2. Most important symptoms a	nd effects, both acute and delayed
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin. Repeated exposure may cause skin dryness or cracking.
Ingestion	Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. Ingestion may cause nausea and vomiting.
4.3. Indication of any immediate	medical attention and special treatment needed
Inhalation	Seek medical attention.
Eye contact	Seek medical attention.
Skin contact	Seek medical attention.
Ingestion	Seek medical attention.
SECTION 5: Firefighting mea	asures

Copyright © 2016 ChemSoft Limited. All rights reserved.



5.1. Extinguishing media	
	Extinguishing media. Alcohol resistant foam. Carbon dioxide (CO2). Dry pwder or water fog. Water spray, fog or mist. Do NOT use water jet.
5.2. Special hazards arising fron	n the substance or mixture
	Flammable liquid and vapour. Vapours are heavier than air. Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	In case of fire and/or explosion do not breathe fumes. Wear:. Self-contained breathing apparatus. Protective equipment.
Further information	
	No data available.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Avoid contact with skin and eyes.
6.2. Environmental precautions	
	Advise local authorities if large spills cannot be contained. Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for co	ntainment and cleaning up
	Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
6.4. Reference to other sections	
	See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.
Further information	
	No data available.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handlin	g
	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Ensure adequate ventilation of the working area.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Keep away from sources of ignition - No smoking.
7.3. Specific end use(s)	
	Used in Industrial applications.
SECTION 8: Exposure control	ols/personal protection
8.1. Control parameters	
	Control noromators
	Control parameters.

8.1.1. Exposure Limit Values



Revision 2 Revision date 2016-07-14

8.1.1. Exposure Limit Values

2-methoxy-1-methylethyl acetate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 274
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 548
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls

Ensure adequate ventilation of the working area.
Vear chemical protective clothing. Suitable foot protection e.g. boots. Wear suitable protective clothing. Wear suitable gloves and eye/face protection.
Approved safety goggles.
Chemical resistant gloves (PVC).
Vear suitable protective clothing and gloves.
Self-contained breathing apparatus.
No data available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	
Odour	
Odour threshold	No data available
pH	No data available
Melting point	No data available
Initial boiling point	110 °C
Flash point	40 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	0.9 (H2O = 1 @ 20 °C)
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	No data available	
Surface tension	No data available	
Gas group	No data available	
Benzene Content	No data available	
Lead content	No data available	
VOC (Volatile organic	836 g/l	
compounds)		
SECTION 10: Stability and reactivity		



2 Revision Revision date 2016-07-14

10.1. Reactivity		
	No data available.	
10.2. Chemical stability	·	
	Stable under normal conditions.	
10.3. Possibility of hazardous re	eactions	
	No data available.	
10.4. Conditions to avoid	•	
-	Heat, sparks and open flames.	
10.5. Incompatible materials		
	Strong oxidising agents.	
10.6. Hazardous decomposition		
	No data available.	
Further information		
	No data available.	
	1	
SECTION 11: Toxicological		
11.1.4. Toxicological Information	n	
2-methoxy-1-methylethyl acetate	Oral Rat LD50: 50 >2000 mg/kg	
Ethyl lactate	Oral Rat LD50: >8,200 mg/kg Inhalation Rat LC50/4 h: no data available	Dermal Rabbit LD50: >5000 mg/kg
Metal Complex Black Dye 29	Dermal Rat LD50: 2000 mg/kg	Oral Rat LD50: 5000 mg/kg
	Oral Mouse LD50: 2.202 mg/kg	Inhalation Rat LC50/4 h: 5.9 mg/kg
SECTION 42. Easteries inf		
SECTION 12: Ecological infe	ormation	
12.1. Toxicity		
12.1. Toxicity 2-methoxy-1-methylethyl acetate	Daphnia EC50/48h: 500 mg/l	Fish LC50/96h: 180 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate	Daphnia EC50/48h: 500 mg/l	
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab 12.3. Bioaccumulative potential	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l bility No data available.	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab 12.3. Bioaccumulative potential	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l bility No data available.	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab 12.3. Bioaccumulative potential Partition coefficient	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l No data available. No data available.	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab 12.3. Bioaccumulative potential	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l No data available. No data available. ADII PME Fast Dry Solvent Black No data available	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradate 12.3. Bioaccumulative potential Partition coefficient 12.4. Mobility in soil	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l sility No data available. ADII PME Fast Dry Solvent Black No data available No data available.	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab 12.3. Bioaccumulative potential Partition coefficient	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l No data available. No data available. ADII PME Fast Dry Solvent Black No data available No data available.	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab 12.3. Bioaccumulative potential Partition coefficient 12.4. Mobility in soil 12.5. Results of PBT and vPvB	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l sility No data available. ADII PME Fast Dry Solvent Black No data available No data available.	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradate 12.3. Bioaccumulative potential Partition coefficient 12.4. Mobility in soil	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 1000 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l ility No data available. ADII PME Fast Dry Solvent Black No data available No data available. No data available.	Fish LC50/96h: 320 mg/l
12.1. Toxicity 2-methoxy-1-methylethyl acetate Ethyl lactate Metal Complex Black Dye 29 12.2. Persistence and degradab 12.3. Bioaccumulative potential Partition coefficient 12.4. Mobility in soil 12.5. Results of PBT and vPvB	Daphnia EC50/48h: 500 mg/l Daphnia EC50/48h: 560 mg/l Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 100 mg/l No data available. No data available. ADII PME Fast Dry Solvent Black No data available No data available.	Fish LC50/96h: 320 mg/l



 Revision
 2

 Revision date
 2016-07-14

Further information	
	No data available.
SECTION 13: Disposal cor	nsiderations
13.1. Waste treatment method	ls
	This product and it's container must be disposed of in accordance with all local and national regulations.
SECTION 14: Transport in	formation
Hazard pictograms	
14.1. UN number	
	UN1210
14.2. UN proper shipping nam	e
	PRINTING INK
14.3. Transport hazard class(e	
ADR/RID	3
Subsidiary risk	
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-
14.4. Packing group	
Packing group	
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
ADR/RID	
Hazard ID	30
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-D
ΙΑΤΑ	
Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L
SECTION 15: Regulatory i	nformation
15.1. Safety, health and enviro	onmental regulations/legislation specific for the substance or mixture

EU Commission Regulation 2015/830/EU: Amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and



ADII PME Fast Dry Solvent Black

Revision date 2016-07-14

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessmenst are still required.

SECTION 16: Other information

Other information	
Revision	This document differs from the previous version in the following areas:.
	2 - Hazard pictograms.
Text of risk phrases in Section	R10 - Flammable
3	R37 - Irritating to respiratory system.
	R41 - Risk of serious damage to eyes.
	R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Text of Hazard Statements in	Flam. Liq. 3: H226 - Flammable liquid and vapour.
Section 3	Eye Dam. 1: H318 - Causes serious eye damage.
	STOT SE 3: H335 - May cause respiratory irritation.
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Maximum content of VOC	836 g/l.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

