ADII ITD

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/7

ADII Hi-Res Food Grade Ink

Revision Revision date 2016-07-14

SECTION 1: Identification of the substance/mixture and of the comp	any/undertaking
--	-----------------

1.1. Product identifier

Product name ADII Hi-Res Food Grade Ink

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Printing Ink.

1.3. Details of the supplier of the safety data sheet

Company

A. D. I.I. Ltd

Address

Houldsworth Mill Business Centre

Houldsworth Street Stockport SK5 6DA

Telephone

Email

Mobile 07590 414092

john@acorndigital.co.uk

1.4. Emergency telephone number

Emergency telephone number

Mobile 07590 414092

24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification -

Xi: R37-41 R10

1999/45/EC

Symbols: Xi: Irritant.

Main hazards

Flammable. Irritating to respiratory system. Risk of serious damage to eyes.

2.1.2. Classification - EC

1272/2008

Flam. Liq. 3: H226; Eye Dam. 1: H318; STOT SE 3: H335;

2.2. Label elements

Hazard pictograms







Signal Word

Prevention

Hazard Statement

Danger

Flam. Liq. 3: H226 - Flammable liquid and vapour. Eye Dam. 1: H318 - Causes serious eye damage.

STOT SE 3: H335 - May cause respiratory irritation.

Precautionary Statement:

P210 - Keep away from heat, hot surfaces, sparks, o

pen flames and other ignition sources. No

smoking.

Revision 8 Revision date 2016-07-14

2.2. Label elements

Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ soap.
Response	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	P403+P235 - Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards No data available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc.	Classification	M-factor.
				Number	(%w/w)		
Ethyl lactate	607-129-00-7	97-64-3	202-598-0			R10 Xi; R37-41	
n-Butyl acetate	607-025-00-1	123-86-4	204-658-1			R10 R66 R67	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc.	Classification	M-factor.
				Number	(%w/w)		
Ethyl lactate	607-129-00-7	97-64-3	202-598-0			Flam. Liq. 3: H226; STOT	
						SE	
						3: H335; Eye Dam. 1: H318;	
n-Butyl acetate	607-025-00-1	123-86-4	204-658-1			Flam. Liq. 3: H226; STOT	
						SE	
SECTION 4: First aid measures						3: H336;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Seek medical attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Treat as for inhalation if any signs of poisoning are present.
Ingestion	DO NOT INDUCE VOMITING. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin. Repeated exposure may cause skin dryness or cracking.
Ingestion	Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention.
Skin contact	Seek medical attention.
Ingestion	Seek medical attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Extinguishing media. Alcohol resistant foam. Carbon dioxide (CO2). Dry pwder or water fog. Water spray, fog or mist. Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture



Revision 8 Revision date 2016-07-14

	Revision date 2010-07-1
5.2. Special hazards arising fro	m the substance or mixture
	Flammable liquid and vapour. Vapours are heavier than air. Burning produces irritating, toxic and
	obnoxious fumes.
5.3. Advice for firefighters	
	In case of fire and/or explosion do not breathe fumes. Wear:. Self-contained breathing apparatus.
	Protective equipment.
Further information	
	No data available.
SECTION 6: Accidental rele	ease measures
6.1. Personal precautions, prof	ective equipment and emergency procedures
	Avoid contact with skin and eyes.
6.2. Environmental precautions	
	Advise local authorities if large spills cannot be contained. Do not allow product to enter drains.
	Prevent further spillage if safe.
6.3. Methods and material for o	containment and cleaning up
	Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of
	water.
6.4. Reference to other section	
	See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste
	treatment information.
Further information	
	No data available.
SECTION 7: Handling and	storage
7.1. Precautions for safe handl	·
	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact
	with skin and eyes. Ensure adequate ventilation of the working area.
7.2. Conditions for safe storage	e, including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Keep away from sources of ignition - No smoking.
7.3. Specific end use(s)	
	Used in Industrial applications.
SECTION 8: Exposure con	
8.1. Control parameters	
o. i. Control parameters	
	Control parameters.
0.1.1 Evacoura Limit Value	Tootiusi parameters.
8.1.1. Exposure Limit Values	WELO believitaness 450
n-Butyl acetate	.,
	WEL 8-hr limit mg/m3 total - WEL 15 min limit mg/m3 total -
	inhalable dust: inhalable dust: WEL 8-hr limit mg/m3 total - WEL 15 min limit mg/m3 total -
	The formation total
	reparable dust reparable dust
n-Butyl acetate	· · · · · · · · · · · · · · · · · · ·

8.2. Exposure controls

Revision 8 Revision date 2016-07-14

8.2. Exposure controls

	No data available.
8.2.1. Appropriate engineering	Ensure adequate ventilation of the working area.
controls 8.2.2. Individual protection	Wear chemical protective clothing. Suitable foot protection e.g. boots. Wear suitable protective clothing. Wear suitable gloves and eye/face protection.
measures	Approved safety goggles.
Eye / face protection	Chemical resistant gloves (PVC).
Skin protection -	
Skiii protection -	Wear suitable protective clothing and gloves.
Handprotection	Self-contained breathing apparatus.
Skin protection - Other	No data available.

Respiratory protection SECTION 9: Physical and chemical properties

Thermal hazards

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Red or Blue
Odour	Mild
Odour threshold	No data available
рН	No data available
Melting point	No data available
Initial boiling point	154 °C
Flash point	46 °C
	No data available
Flammability (solid, gas)	
Vapour pressure	No data available
Vapour density	No data available
Relative density	1.01 (H2O = 1.@.20 °C)
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	140 data available
Explosive properties	
Oxidising properties	No data available
Solubility	Slightly soluble in water

9.2. Other information

	_
Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic	868 g/l
compounds)	
OFOTION 40 OUT 1111	17 - 27

SECTION 10: Stability and reactivity

	No data available.
10.2. Chemical stability	
	Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

Revision Revision date 2016-07-14

10.4. Conditions to avoid Heat, sparks and open flames. 10.5. Incompatible materials Strong oxidising agents. 10.6. Hazardous decomposition products No data available. Further information No data available. SECTION 11: Toxicological information 11.1.4. Toxicological Information Ethyl lactate Dermal Rabbit LD50: >5000 mg/kg Oral Rat LD50: >8,200 mg/kg Inhalation Rat LC50/4 h: no data available SECTION 12: Ecological information 12.1. Toxicity Ethyl lactate Daphnia EC50/48h: 560 mg/l Fish LC50/96h: 320 mg/l 12.2. Persistence and degradability No data available. 12.3. Bioaccumulative potential No data available. Partition coefficient ADII Hi-Res Food Grade Ink No data available 12.4. Mobility in soil No data available. 12.5. Results of PBT and vPvB assessment No data available.

12.6. Other adverse effects

No data available.

Further information

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

This product and it's container must be disposed of in accordance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms





Revision 8 Revision date 2016-07-14

	Revision date 2016-07-14
14.1. UN number	
	UN1210
14.2. UN proper shipping name	
	PRINTING INK
14.3. Transport hazard class(es)	
ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-
14.4. Packing group	
Packing group	III
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
ADR/RID	
Hazard ID	30
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-D
IATA	
Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction	355
(Passenger)	
Maximum quantity	60 L
SECTION 15: Regulatory info	ormation
15.1. Safety, health and environr	mental regulations/legislation specific for the substance or mixture
	EU Commission Regulation 2015/830/EU: Amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
15.2. Chemical safety assessme	ent
	This product contains substances for which Chemical Safety Assessmenst are still required.
SECTION 16: Other informat	ion
Other information	
Revision	This document differs from the previous version in the following areas:.
	2 - Precautionary Statement: Prevention.2 - Precautionary Statement: Response.2 - Precautionary Statement: Storage.2 - Precautionary Statement: Disposal.
Text of risk phrases in Section 3	R10 - Flammable R37 - Irritating to respiratory system. R41 - Risk of serious damage to eyes. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.

Revision 8 Revision date 2016-07-14

Other information		
Text of Hazard Statements in Section 3	Flam. Liq. 3: H226 - Flammable liquid and vapour. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation.	
	EUH066 - Repeated exposure may cause skin dryness or cracking.	
	STOT SE 3: H336 - May cause drowsiness or dizziness.	
Maximum content of VOC	868 g/l.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	